




## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<b>(51) International Patent Classification <sup>7</sup> :</b>  <b>G02B 6/00</b>	<b>A1</b>	<b>(11) International Publication Number:</b> <b>WO 00/42456</b>  <b>(43) International Publication Date:</b> 20 July 2000 (20.07.00)
<b>(21) International Application Number:</b> PCT/US00/01094  <b>(22) International Filing Date:</b> 14 January 2000 (14.01.00)  <b>(30) Priority Data:</b> 60/115,830      14 January 1999 (14.01.99)      US  <b>(71) Applicant (for all designated States except US):</b> FEDERAL-MOGUL CORPORATION [US/US]; 26555 Northwestern Highway, Southfield, MI 48034 (US).  <b>(72) Inventor; and</b> <b>(75) Inventor/Applicant (for US only):</b> HULSE, George, Robert [US/US]; 1542 Dellwood Avenue, Cookeville, TN 38506 (US).  <b>(74) Agent:</b> STEVENS, James, D.; Reising, Ethington, Barnes, Kisselle, Learman & McCulloch, P.C., P.O. Box 4390, Troy, MI 48099 (US).		<b>(81) Designated States:</b> AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).  <b>Published</b> <i>With international search report.</i>

**(54) Title:** WAVEGUIDE ASSEMBLY FOR LATERALLY-DIRECTED ILLUMINATION IN A VEHICLE LIGHTING SYSTEM

**(57) Abstract**

A distributed lighting system (10) comprising a waveguide assembly that includes a vehicle interior trim panel (28) having an elongated opening (30) therein and a correspondingly elongated waveguide (12) attached to the trim panel to provide laterally-directed illumination through the opening along the length of the waveguide. The waveguide (12) is attached to the trim panel (28) using a support frame (18) that includes a light-transmissive lower wall (20) which fits within the opening (30) and a pair of opposed side walls (22) that, together with the lower wall, define a channel (24) in which the waveguide is located. The waveguide (12) includes a light-scattering region (52) located opposite the opening (30) in the trim panel (28) to direct light laterally out of the waveguide and through the opening. The waveguide assembly (10) also includes a back cover (40) that encloses the waveguide (12) between the cover (40) and support frame (18). Different waveguide cross-sections and light-scattering configurations are disclosed.

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

## WAVEGUIDE ASSEMBLY FOR Laterally-DIRECTED ILLUMINATION IN A VEHICLE LIGHTING SYSTEM

### TECHNICAL FIELD

5

This invention relates generally to lighting systems for automotive vehicles and more particularly to distributed lighting systems wherein light from a remote source is transmitted via a waveguide to desired areas within the interior of the vehicle.

10

### BACKGROUND OF THE INVENTION

Distributed lighting systems (DLS's) are sometimes used in automotive interior lighting applications for directing light from a central source via optical fibers or other waveguides to illuminate selected areas of the interior of the vehicle. Many of such applications are directed toward illuminating instrument panels, controls, and the like in lieu of providing individual light sources for each location, such as incandescent or LED lamps.

20

In some instances, these distributed lighting systems use waveguides to route light to a remote location where it is emitted out of the end of the waveguide to provide back lighting or to provide illumination within the vehicle interior. Control of the light emitted from the ends of the waveguides can be accomplished using lenses or other optical elements. Rather than using a waveguide simply to carry light to a remote location, it is known to provide notches and other such surface features along the length of the waveguide to promote the lateral emission of light from the waveguide. See, for example, U.S. Patent No. 5,845,038 to D.J. Lundin et al. As indicated in U.S. Patent No. 5,659,643 to R.H. Appeldorn et al., it is also known to use waveguides of varying cross-sectional shape for this purpose.

30

To properly provide lengthwise illumination in a vehicle application using waveguides, some type of practical mounting assembly is required that permits the waveguide to be securely mounted in place while  
5 maintaining the desired illumination characteristics for the intended application. Accordingly, it is a general object of the invention to provide a directed lighting system which is particularly advantageous for use in connection with interior trim panels such as headliners, door panels, seat panels, visors, and the like to illuminate the cabin of a vehicle, including  
10 the floor of the vehicle, to provide an aesthetically pleasing yet effective illumination of the interior of the vehicle.

#### SUMMARY OF THE INVENTION AND ADVANTAGES

15 According to the invention, a distributed lighting system is provided having an elongated waveguide fabricated of light-transmissive material mounted on a support frame having a protective light-transmissive lens adjacent the waveguide opposite a light-scattering region of the waveguide for transmitting the light scattered by the region through the lens portion to  
20 light the interior of a vehicle.

The support frame is constructed to mount to an interior panel of a vehicle, such as a headliner, door panel, instrument panel, seat panel, or the like with the lens region of the support frame extending through a  
25 correspondingly shaped opening in the interior trim panel and the waveguide supported and concealed beneath the panel. The support frame is secured by suitable means to the trim panel, such as by mechanical fasteners, self-retaining connectors, or the like.

30 A reflective backing cover preferably extends and shrouds an exposed back surface region of the waveguide opposite the lens for redirecting any light that would otherwise escape through the back surface

back into the waveguide for transmission through the lens. The cover may advantageously have connecting portions cooperating with associated connecting portions of the support frame for securing the waveguide within the channel.

5

### BRIEF DESCRIPTION OF THE DRAWINGS

These and other features and advantages of the present invention will become more readily appreciated when considered in connection with the following detail description and appended drawings, wherein:

10

Figure 1 is an exploded fragmentary perspective view of a distributed lighting system constructed according to a first presently preferred embodiment of the invention;

15

Figure 2 is an enlarged cross-sectional view of the assembled components of Figure 1 taken generally along lines 2-2 of Figure 1;

20

Figures 3-5 are three alternative cross-sectional shapes that may be employed with the waveguide in lieu of the circular shape illustrated in the preceding figures;

25

Figure 6 is still a further alternative construction of a waveguide having a variable width light-scattering region; and

Figure 7 is yet another embodiment of a waveguide having integrated mounting features.

### DETAILED DESCRIPTION

30

A distributed light system (DLS) constructed according to a first presently preferred embodiment of the invention is shown generally at 10 in

- 4 -

Figures 1 and 2 and comprises a waveguide 12 extending longitudinally between a light input end 14 and an opposite end 16 and being fabricated of a solid body of light-transmissive material such as acrylic or the like.

5           The DLS 10 includes a support frame 18 having a lower wall 20 and opposite laterally spaced side walls 22 defining a longitudinally extending channel 24 in which the waveguide 12 is disposed. At least the lower wall 20 and preferably the entire support frame 18 is fabricated of a light-transmissive material such as acrylic so that the lower wall 20 serves as a  
10       protective light-transmitting lens for the waveguide 12, as will be explained in greater detail below.

As shown best in Figure 2, the side walls 22 preferably have a stepped profile defining opposite longitudinally extending outer shoulders  
15       26 adjacent the lens 20. The stepped shoulders 26 enable the support frame 18 to be mounted on an interior trim panel 28 of an automotive vehicle with the lens portion 20 of the frame 18 projecting into a correspondingly shaped opening 30 in the panel 28. The panel 28 may comprise a headliner, a door panel, seat panel, visor, instrument panel, etc. With such an arrangement,  
20       only the lens portion 20 of the frame 18 is visible on the finished interior side 32 of the trim panel 28. The remaining portions of the frame 18 and components of the DLS 10 are disposed and concealed behind the panel 28 on a back side 34 thereof.

25           The support frame 18 is provided with some means of securing the frame 18 and thus the DLS 10 to the panel 28. It will be appreciated that any of a number of fastening systems commonly used in the interior trim and lighting art may be employed, and may include a variety of mechanical fastening systems such as spring clips, self-retaining locking projections,  
30       adhesives, or simply screws 36, as illustrated in the drawings. The screws 36 extend through openings provided in screw mount portions 38 of the

- 5 -

frame 18 projecting laterally outwardly of the side walls 22 on opposite sides of the channel 24 adjacent the shoulders 26 and are operative for securing the frame 18 to the trim panel 28 in the manner illustrated in Figure 2. It will be appreciated from Figure 1 that the frame 18 may be provided with a plurality of such screw mount portions 38 provided at spaced locations along the length of the frame 18.

One way of securing the waveguide 12 within the channel 24 of the frame 18 is by provision of a back cover 40 which fits over an exposed back side portion 42 of the waveguide 12 and is secured to the frame 18 thereby capturing the waveguide 12 between the frame 18 and cover 40 as shown best in Figure 2. For purposes of securing the cover 40 to the frame 18, the cover may have similar screw mount portions 44 projecting from opposite lateral sides of the cover in alignment with the screw mount portions 38 of the frame 18 to accommodate the reception of the screws 36, such that the cover 40 may be simultaneously joined to the frame 18 and secured to the panel 28 via the screws 36. It will be appreciated, however, that any of a number of means may be employed to secure the cover 40 to the frame 18, such as adhesives, interlocking portions, welding, etc. Unlike the lens portion 20 of the frame 18, the cover 40 is non-transmissive of light (i.e., is opaque) and preferably has a reflective inner surface 46 that conforms closely in size and shape to that of the back side portion 42 of the waveguide 12 so as to redirect any light rays that would otherwise escape through the back side portion 42 of the waveguide 12 back into the waveguide 12 for transmission through the lens 20.

The waveguide 12 is operatively coupled at its light input end 14 to a source of light 48. The light source 48 may comprise an incandescent or LED lamp, or input from optical fibers or another waveguide. It is contemplated that the DLS 10 may thus comprise either a stand alone light system having its own light source 48 for directing light into the waveguide

12 through the input end 14, or may comprise a section of an overall larger distributed lighting system in which case the DLS 10 of the invention may comprise one of several branches of a multi-branch distributed lighting system of a vehicle.

5

The light which enters the waveguide 12 from the light source 48 is transmitted therealong toward the opposite end 16, and during its passage is reflected off the outer surface 50 of the waveguide 12 interiorly thereof according to known principles. To achieve internal reflection, the outer  
10 surface 50 of the waveguide 12 is generally smooth and free of imperfections that would act to defract the light. According to the invention, however, a select region 52 of the outer surface 50 of the waveguide 12 opposite the lens 20 is roughened such that the light encountering the region 52 is scattered. Some of the scattered light rays are  
15 directed toward the opposite side of the waveguide 12 where they are transmitted out of the waveguide 12 and through the lens 20 into an interior compartment 54 of a vehicle 56. The roughened light-scattering region 52 extends longitudinally of the waveguide 12 and, in the illustrated embodiment, is continuous between the ends 14, 16 of the waveguide 12. It  
20 is contemplated that there may be applications in which it may not be necessary or desirable to transmit the light from the waveguide 12 over its entire length, and in such instances the roughened light-scattering regions 52 may be interrupted by intervening smooth surface sections 50 along which the light would be internally reflected rather than transmitted out of  
25 the waveguide 12.

Any of a number of techniques may be employed to form the light-scattering region 52, and may include molding a roughened region 52 into the waveguide 12 during its formation, or by any of a number of post  
30 forming operations such as bead blasting, scribing, application of light-defracting tape, or other means which would act to scatter the light rays that



encounter the region 52 so as to direct at least some of the defracted rays through the lens 20.

It will be observed from Figure 2 that the light-scattering region 52 is straddled on either lateral side by smooth light-reflecting portions 50 of the outer surface which reflect and redirect the light inwardly of the waveguide with minimal scattering. Restricting the width and location of the light-scattering region 52 relative to the lens 20 results in a directed beam of light rays being transmitted through the lens 20. In the embodiment of Figures 1 and 2, the waveguide 12 has a solid circular cross-sectional shape, which acts to focus and collimate a portion of the scattered light rays R which are directed and transmitted through the lens 20 to provide an intense, directed beam of light into the interior 54 of the vehicle 56 as illustrated diagrammatically in Figure 2.

Figures 3 and 4 show alternative waveguide cross-sectional shapes wherein the same reference numerals used in connection with the waveguide 12 are employed but are offset by increments of 100 and 200, respectively, to indicated like parts. Each of the waveguides 112, 212 of Figures 3 and 4 have curved lens configurations which act to focus and collimate some of the scattered light rays into a directed beam R for transmission through the support frame lens 20. The waveguide 112 of Figure 3 has a parabolic cross-sectional shape which would serve to intensify the focusing the collimation of the scattered light rays to produce a high intensity beam of light R. The waveguide 212 illustrated in Figure 4 has a flat, planar back side surface 242 on which the roughened region 252 is formed, causing light to be scattered in a nondirected manner. However, the opposite side of the waveguide adjacent the lens 20 has an exterior concave profile which would act to align and collimate some of the scattered light rays to provide an intense beam of light R transmitted through the lens 20.

Figure 5 illustrates still a further embodiment 312 of the waveguide having a rectangular profile wherein the same reference numerals are employed for like features, but offset by 300. Such may be used in conjunction with a curved frame lens 20 having light-focusing characteristics for generating a similar directed beam of light into the interior 54 of the vehicle 56.

Some of the light entering the waveguide 12 through the light input end 14 will reach the opposite end 16 without having been transmitted through the lens 20. The end 16 may be capped off with reflective silver tape or the like so as to redirect the light back through the waveguide 12 toward the input end 14 to intensify the emission of light through the lens 20. Alternatively, the opposite end 16 may be coupled with a waveguide or fiber(s) of another DLS to serve as a light input source thereto.

As the light travels along the waveguide 12, it may have a tendency to lose some of its intensity as it nears the opposite end 16 relative to the intensity of the light adjacent the input end 14. To counteract such a problem, a waveguide 412 having an alternative construction is illustrated in Figure 6 wherein again like reference numerals have been used to represent like features, but offset by 400. The roughened region 452 of the waveguide 412 is tapered so as to be wider adjacent the opposite end 416 and gradually narrowing toward the input end 414. This provides a relatively greater amount of light scattering adjacent the opposite end 416 to compensate for the reduced intensity there resulting from light lost laterally out of the waveguide 412 along its length.

Figure 7 shows still another alternative embodiment of the waveguide 512 (corresponding reference numerals used, offset by 500) which is generally like that illustrated in and described in Figures 1 and 2 except for provision of integrated mounting features for securing the

5 waveguide 512 to the support frame 18, which may take the form of compatible screw mount portions 60 that align and cooperate with the screw mount portions 38 of the frame 18 for accepting the screws 36 to join the waveguide 512 to the frame 18. With this embodiment of the waveguide 512, the fastened cover 40 may be omitted and, if desired, reflective tape 70 may be applied to the exposed back side portion 542 of the waveguide 512 for reflecting any scattered light that would otherwise escape through the back side portion 542 back into the waveguide 512. Beneath the tape 70 or incorporated into the inner surface of the tape 70 is a light-scattering region 552 as described previously.

15 The invention thus contemplates a DLS having a waveguide mounted in a support frame formed with a protective light-transmitting lens portion opposite a light-scattering region of the waveguide which is operative to scatter light introduced into the waveguide causing some of the light to be transmitted out of the waveguide through the lens.

20 It is further contemplated that such a DLS be mounted in an interior trim panel of an automotive vehicle, such as a headliner, door panel, instrument panel, seal panel, etc., with the lens of the frame accommodated in an opening of the panel and the remaining portions of the frame and components of the DLS concealed behind the panel.

25 The invention further contemplates waveguides having a number of different cross-sectional shapes with at least some of which having a concave exterior profile acting in conjunction with the light-scattering region to focus and collimate some of the scattered light rays that are directed toward the lens of the support frame to provide a high intensity light beam into the interior of a vehicle.

30

5 It will thus be apparent that there has been provided in accordance with the present invention a waveguide assembly which achieves the aims and advantages specified herein. It will of course be understood that the foregoing description is of preferred exemplary embodiments of the invention and that the invention is not limited to the specific embodiments shown. Various changes and modifications will become apparent to those skilled in the art and all such variations and modifications are intended to come within the scope of the appended claims.

CLAIMS

I claim:

- 5           1. A waveguide assembly for providing illuminating light through an opening in a vehicle panel, comprising:
- an elongated support frame having a lower wall extending laterally between two opposing side walls, said lower wall and side walls extending longitudinally to thereby form an elongated channel, said lower wall having
- 10           a shape that corresponds to the opening in the vehicle panel such that said lower wall fits within the opening when said support panel is assembled to the panel; and
- a waveguide located in said channel and extending longitudinally along the length of said channel, said waveguide having first and second
- 15           ends such that light entering said waveguide at said first end travels through said waveguide along the length of said channel towards said second end;
- wherein said waveguide and said lower wall of said support frame are both constructed of a light-transmissive material with said waveguide having a light-scattering region oriented relative to said lower wall such
- 20           that at least a portion of the light travelling through said waveguide impinges upon said light-scattering region and is directed laterally out of said waveguide and through said lower wall of said support frame.
2. A waveguide assembly as defined in claim 1, wherein said
- 25           waveguide is oriented such that said light-scattering region is located opposite said lower wall.
3. A waveguide assembly as defined in claim 1, wherein said light-scattering region is continuous along the length of said waveguide.

- 12 -

4. A waveguide assembly as defined in claim 1, wherein said light-scattering region is narrower at said first end than at said second end.

5        5. A waveguide assembly as defined in claim 1, wherein said support frame includes longitudinally-extending outer shoulders adjacent said lower wall.

10       6. A waveguide assembly as defined in claim 1, wherein said waveguide includes at least one pair of lateral projections extending away from said channel.

15       7. A waveguide assembly as defined in claim 1, wherein said side walls each include at least one lateral projection extending away from said channel.

8. A waveguide assembly as defined in claim 1, further comprising a cover enclosing said waveguide within said channel.

20       9. A waveguide assembly as defined in claim 8, wherein said cover includes a reflective surface extending along the length thereof, said reflective surface being oriented to reflect light laterally exiting said waveguide such that the exiting light is reflected back into said waveguide in a direction generally towards said lower wall.

25       10. A waveguide assembly as defined in claim 1, wherein said waveguide has a circular cross-sectional shape.

30       11. A waveguide assembly for providing vehicle interior illumination, comprising:

      a vehicle interior panel having front and back sides and an opening therein;

- 13 -

a support frame having a lower wall formed of light-transmissive material, said support frame being mounted to the back side of said interior panel such that said lower wall extends into the opening in said interior panel with only said lower wall being visible from the front side of said panel; and

a waveguide attached to said support frame and concealed by said lower wall behind the opening in said interior panel, said waveguide having a light-scattering region oriented relative to said lower wall such that light traveling through said waveguide is deflected out of said waveguide and through said lower wall to thereby provide interior vehicle illumination.

12. A waveguide assembly as defined in claim 11, wherein said opening comprises a longitudinally-extending opening and said waveguide and support frame extend longitudinally along the length of said opening.

13. A waveguide assembly as defined in claim 12, wherein said support frame further includes a pair of opposing side walls extending longitudinally along the length of said opening with said lower wall extending laterally between said side walls, whereby said lower wall and side walls together define an elongated channel, and wherein said waveguide is disposed in said channel.

14. A waveguide assembly as defined in claim 11, wherein said lower wall includes a front surface that is flush with said front side of said interior panel.

15. A waveguide assembly as defined in claim 11, wherein said support frame includes a plurality of lateral projections extending away from said lower wall in contact with said back side of said interior panel.

16. A waveguide assembly as defined in claim 11, wherein said

- 14 -

support frame includes longitudinally-extending outer shoulders adjacent said lower wall.


5        17. A waveguide assembly as defined in claim 11, wherein said waveguide is oriented such that said light-scattering region is located opposite said lower wall.

10       18. A waveguide assembly as defined in claim 11, further comprising a cover enclosing said waveguide between said cover and said support frame.

15       19. A waveguide assembly as defined in claim 18, wherein said cover includes a reflective surface extending along the length thereof, said reflective surface being oriented to reflect light laterally exiting said waveguide such that the exiting light is reflected back into said waveguide in a direction generally towards said lower wall.

20. A waveguide assembly as defined in claim 11, wherein said waveguide has a circular cross-sectional shape.



FIG -1





FIG-3




FIG - 4




FIG - 5




FIG - 6




FIG - 7

## INTERNATIONAL SEARCH REPORT

International application No.  
PCT/US00/01094

## A. CLASSIFICATION OF SUBJECT MATTER

IPC(7) :G02B 6/00

US CL :385/147, 901, 31; 362/560

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 385/147, 901, 31, 32, 47, 123, 124, 125; 362/560, 554, 556

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched  
NONE

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

USPTO APS WAVEGUIDES\$1 SAME ILLUMINATS\$3 AND ELONGATED AND VEHICLES\$1; (OPTICAL ADJ FIBER\$1 OR OPTICAL ADJ FIBRES\$1)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5,659,643 A (APPELDORN et al.) 19 August 1997 (19-08-1997), see figure 1 and Abstract.	1-20
A	US 5,845,038 A (LUNDIN et al.) 01 December 1998 (01-12-1998), see Figure 2 and Abstract.	1-20

☐ Further documents are listed in the continuation of Box C. ☐ See patent family annex.

* Special categories of cited documents:	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
"A" document defining the general state of the art which is not considered to be of particular relevance	"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
"E" earlier document published on or after the international filing date	"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	"&" document member of the same patent family
"O" document referring to an oral disclosure, use, exhibition or other means	
"P" document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search

05 APRIL 2000

Date of mailing of the international search report

21 APR 2000

Name and mailing address of the ISA/US  
Commissioner of Patents and Trademarks  
Box PCT  
Washington, D.C. 20231

Facsimile No. (703) 308-4848

Authorized officer

PHAN T. H. PALMER

Telephone No. (703) 308-4848

THIS PAGE BLANK (USPTO)